



VACTOR
HYDRO excavator

VACTOR

HXX SPECIFICATIONS



Overall Length	CA	Height	Width
420 in. (10.67 m)	194 in. (4.93 m)	156 in. (3.96 m)	102 in. (2.59 m)

Debris Body

- .1/4 in. (6.35 mm) Abrasion- and Corrosion-Resistant Steel
- J/4-Size Rear Door; Hydraulically Opened and Locked
- 50-Degree Dump Body
- 5-Year Warranty against Corrosion

Vacuum System

- 8,000 cfm (227 m³/j) Dual Centrifugal Fans Hydrostatically Driven by Crank-shaft PTO Off-Chassis Engine
- Dual Stainless-Steel Float Balls
- Five-Year Fan Warranty

Hot Water Heater

- 380,000 BTU (111 kw) Capacity
- Operated while Driving, Idling or Excavating
- Dial Thermostat for Temperature Control
- Weather-Resistant Enclosure

Water Pump

- Pump Rated for 13 gpm (49 l) at 2,500 psi (172 bar)
- Hydraulically Driven, Variable Pressure Piston Pump
- Surge Suppressor

- Independent Flow and Pressure Capabilities
- Installed in Heated Pump Cabinet

Water Tank

- 1,300-Gallon (4921 l), Single-Cell Design for Freeze Resistance
- Stainless-Steel (#304) Construction
- Electronic Water Level Gauge
- Curbside Fill Connection with Anti-Siphon Device
- 10-Year Warranty against Corrosion

Boom

- Hydraulic, 4.5 ft. (1.4 m) Extendible Boom
- Self-Adjusting, High-Pressure Seals between Boom and Debris Body
- Remote Pendant Control with 75 ft. (22.9 m) Cord Includes Vacuum Relief and Pump On/Off
- Secondary Joystick Boom Control on Control Panel
- 8 in. (0.2 m) 1.0. on All Hoses and Boom Vacuum Tubes

Popular Options

- 7 ft. (2.1 m) Hydraulic Telescopic Boom with 320-Degree Rotation
- Cold Weather Re-circulating System

- Wireless Remote Control for Boom with Water Pump Control and Vacuum Relief
- 840,000 BTU (246 kw) Water Heater
- Air Purge System Utilizing Chassis Air System
- 23 gpm (87 l) @ 2,500 psi (172 bar) Water Pump
- Second Operator Station
- Hydraulic Tool Package
- Numerous Light (and Signaling) Options
- Rear Door Splash Shield

Tool Box Option

- 52 in. (1.32 m) W x 24 in. (0.61 m) D x 24 in. (0.61 m) H Aluminum Tool Box (max. 4) above Tandem Axle
- 18 in. (0.46 m) W x 24 in. (0.61 m) D x 48 in. (1.22 m) H Aluminum Tool Box (max. 2) Located behind Tandem Axle
- 58 in. (1.47 m) W x 30 in. (0.76 m) D x 48 in. (1.22 m) H Aluminum Tool Box Located in Front of Tandem Axle, Left Side

Warranty Coverage

Your unit is covered for any defects in material or components for one year from in-service date. The dual-stage fan has a five-year warranty. The stainless-steel water tank has a 10-year warranty against corrosion. See warranty certificate for details.

For a Demonstration or Information, Contact:

Environmental Products of Florida
1158 Elbow Way
Winter Garden, Florida 34787
(407) 798-0004

Phone: (815) 672-3171
Fax: (815) 672-2778
Web: www.vactor.com

VACTOR
Since 1954

2007 International model 7600 chassis with 66,000GVWR.

- CAT C13 diesel engine, 430hp @ 2100rpm, 1550 lb-ft torque
- Fuller FRO-15210C 10 speed manual transmission
- Air conditioning
- AM/FM radio
- Air ride seat
- Cruise control
- 12 cubic yard debris body
- W' abrasion and corrosion resistant Ex-Ten steel
- Flat rear door with hydraulic locks and hydraulic open/close
- 6" knife valve with 10' drain hose and cam-loc connector
- 8" inspection port, top of body with ladder
- Dump angle 50 degrees
- Dual air ports with dual 10" diameter stainless steel float ball
- 1300 gallons capacity #304 stainless steel water tank
- Anti-siphon device with 25' water fill hose
- Mark III electronic low water warning system
- 10 year water tank warranty
- Water system rated 10gpm @ 2500psi
- Hydraulic operated Tri-Plex piston water pump
- Variable flow and pressure
- Handgun hose 3/8" x 75' with operating pressure of 3500psi, burst 14,500psi
- Dual 38" diameter aluminum two-stage centrifugal vacuum compressor
- Hydrostatic fan drive system
- Vacuum relief system
- Remote push button pendant control with 75' cable
- Joystick control for boom
- 7' hydraulic telescopic boom with 320 degrees rotation
- 8" LD. wire reinforced rubber suction hose
- 25' aluminum vacuum pipe
- 3 digging wands with 20' of extensions and valve
- Hydraulic reservoir 65 gallons
- Circuit breakers
- Tow hooks
- Back up alarm
- Folding pipe rack on rear door
- Splash shield on rear door
- Lube manifold
- Electric vibrator for body
- Wireless remote control for boom
- Hydraulic tool package
- Hydraulic shut off valves
- Arrowboard on rear door

- Handlight with retractable reel
- Strobe light on front and rear
- Worklight at operator station
- Worklights on boom
- 2 HXX manuals
- (1) 50" x 30" x 30" aluminum tool box
- (2) 18" x 24" x 48" aluminum tool boxes
- (2) 104" x 24" x 24" aluminum tool boxes
- Chevron reflective tape on rear door
- Training by factory rep.
- Warranty 1 year parts and labor

Chassis Price	\$80,075.00
Vactor Body Price	\$196,165.00
Total delivered price	\$276,240.00

*****Option for Allison 4500RDS automatic transmission \$18,100.00*****